

February 29, 2016

Scott Nelson United States Environmental Protection Agency Office of Federal Activities International Compliance Assurance Division Ariel Rios Building: (2254 A) 1200 Pennsylvania Avenue, NW Washington, DC 20460

RE: CY 2015 Annual Hazardous Waste Export Report

Dear Mr. Nelson:

Please find attached U. S. Chrome Corporation of New York's (USC) CY 2015 annual Hazardous Waste Export Report. The completion of this document was based upon Hazardous Waste Manifests and shipment volumes provided by Stablex of Canada. A copy of the latest Hazardous Waste Reduction Plan (revised June 2015 is attached, as required.

If you have any questions concerning the information presented, please contact me directly.


Very truly your,

U.S. Chrome Corporation of New York

Muchael Klotzbuch

Michael Klotzbach General Manager

Attachment



### CY 2015 Export Report Attachment 1

Hazardous Waste Export Reports

1. PRIMARY EXPORTER (Consignor)

Name:

U.S. Chrome Corporation of New York NYD990774206

USEPA ID#:

31 Swan Street

Mailing Address:

Batavia, New York 14020

Site Address:

31 Swan Street

Batavia, New York 14020

2. EXPORT INTERMEDIARY

Name:

Gulfstream TLC, Inc. NYR000156539

USEPA ID#: Mailing Address:

1080 Military Turnpike Unit 410 Plattsburg, New York 12901

CONSIGNEE

Name:

Stablex Canada, Inc. NYD980756415

USEPA ID#: Mailing Address:

760 Boul. Industriel

Blainsville, Quebec J7C 3V4

TRANSPORTER #1

Name: USEPA ID#: Transport Rollex Ltee

NYF006000053

WASTE INFORMATION

Description: EPA Waste #: Waste Water Treatment Filter Cake

DOT Shipping Name:

RQ Waste Environmentally Hazardous

Substances, Solids nos

DOT Hazard Class:

UN3077

DOT ID Code:

6. SHIPPING INFORMATION

Total Shipments:

Shipment Dates: Total Volume Shipped: 7/21/15 0.75 tons

7. WASTE MINIMIZATION

Report attached.

8. CERTIFICATION

I certify under the penalty of the law that I have personally examined and am familiar with the information submitted in this report, and that based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information including the possibility of fine and imprisonment.

Date: 02/29/2016

PRIMARY EXPORTER (Consignor)

Name: U.S. Chrome Corporation of New York

USEPA ID#: NYD990774206 Mailing Address: 31 Swan Street

Batavia, New York 14020

Site Address: 31 Swan Street

EXPORT INTERMEDIARY

Name: Gulfstream TLC, Inc. USEPA ID#: NYR000156539

Mailing Address: 1080 Military Turnpike Unit 410

Plattsburg, New York 12901

Batavia, New York 14020

CONSIGNEE

Name: Stablex Canada, Inc. USEPA ID#: NYD980756415
Mailing Address: 760 Boul. Industriel

Blainsville, Quebec J7C 3V4

4. TRANSPORTER #1

Name: Transport Rollex Ltee USEPA ID#: NYF006000053

WASTE INFORMATION

Description: Chrome Contaminated Debris

EPA Waste #: D007, D008

DOT Shipping Name: RQ Waste Environmentally Hazardous

Substance Solid nos

DOT Hazard Class: 9

DOT ID Code: UN3077

6. SHIPPING INFORMATION

Total Shipments: 3

Shipment Dates: 4/8/15, 7/21/15 & 11/13/15

Total Volume Shipped: 5.1 tons

WASTE MINIMIZATION Report attached.

CERTIFICATION

I certify under the penalty of the law that I have personally examined and am familiar with the information submitted in this report, and that based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information including the possibility of fine and imprisonment.

PRIMARY EXPORTER (Consignor)

Name: U.S. Chrome Corporation of New York

USEPA ID#: NYD990774206 Mailing Address: 31 Swan Street

Batavia, New York 14020

Site Address: 31 Swan Street

Batavia, New York 14020

2. EXPORT INTERMEDIARY

Name: Gulfstream TLC, Inc. USEPA ID#: NYR000156539

Mailing Address: 1080 Military Turnpike Unit 410 Plattsburg, New York 12901

CONSIGNEE

Name: Stablex Canada, Inc. USEPA ID#: NYD980756415
Mailing Address: 760 Boul. Industriel

Blainsville, Quebec J7C 3V4

4. TRANSPORTER #1

Name: Transport Rollex Ltee USEPA ID#: NYF006000053

WASTE INFORMATION

Description: Waste Chromic Acid Solution

EPA Waste #: D002, D007

DOT Shipping Name: RQ Waste Chromic Acid Solution

DOT Hazard Class: 8

DOT ID Code: UN1755

SHIPPING INFORMATION

Total Shipments: 3

Shipment Dates: 4/8/15, 7/21/15 & 11/12/15

Total Volume Shipped: 2.1 tons

WASTE MINIMIZATION

Report attached.

8. CERTIFICATION

I certify under the penalty of the law that I have personally examined and am familiar with the information submitted in this report, and that based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information including the possibility of fine and imprisonment.

Signed

Date: 02/29/2016

5

PRIMARY EXPORTER (Consignor)

Name: U.S. Chrome Corporation of New York

USEPA ID#: NYD990774206 Mailing Address: 31 Swan Street

Batavia, New York 14020

Site Address: 31 Swan Street

Batavia, New York 14020

2. EXPORT INTERMEDIARY

Name: Gulfstream TLC, Inc. USEPA ID#: NYR000156539

Mailing Address: 1080 Military Turnpike Unit 410 Plattsburg, New York 12901

CONSIGNEE

Name: Stablex Canada, Inc. USEPA ID#: NYD980756415
Mailing Address: 760 Boul. Industriel

Blainsville, Quebec J7C 3V4

TRANSPORTER #1

Name: Transport Rollex Ltee USEPA ID#: NYF006000053

WASTE INFORMATION

Description: Spent Chromic Acid Tank Bottom Sludge

USEPA Waste #: D002, D007

USDOT Shipping Name: RQ Waste Corrosive Solid, Acidic, Inorganic nos

USDOT Hazard Class: 8

USDOT ID Code: UN3260

6. SHIPPING INFORMATION

Total Shipments:

Shipment Dates: 11/12/15 Total Volume Shipped: 0.35 tons

WASTE MINIMIZATION

Report attached.

8. CERTIFICATION

I certify under the penalty of the law that I have personally examined and am familiar with the information submitted in this report, and that based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information including the possibility of fine and imprisonment.

### CY 2015 Export Report Attachment 2

Current Hazardous Waste Reduction Plan

### HAZARDOUS WASTE REDUCTION PLAN 2014 Biennial Update

Prepared For:
U.S. Chrome Corporation of New York
31 Swan Street
Batavia, New York

Prepared By:
Hazard Evaluations, Inc.
3752 North Buffalo Road
Orchard Park, New York 14127

June 30, 2015

### 1.0 INTRODUCTION

### 1.1 Background

The U.S. Chrome Corporation of New York (USC) facility, located at 31 Swan Street, Batavia, New York, specializes in Hard Chrome electroplating of metal parts. The operations performed on-site to produce the facility's end products include very limited machining of metal parts, alkaline cleaning, non-cyanide Chromium electroplating and rinsing. Hazardous waste generation is related primarily to the cleaning and processing of metal parts and the treatment of the resulting wastewaters. The alkaline cleaning involves use of a caustic solution, while the electroplating bath consists of a solution containing Hexavalent Chromium. In 2014, there were six different hazardous waste streams generated by the facility, including: 1) Hazardous wastewater treatment plant filter cake; 2) Chromium contaminated debris; 3) Waste Chromic Acid solution; 4) Alkaline Stripping Solution; 5) Chromic Acid Tank Sludge; and 6) Electroplating process wastewater. The electroplating process wastewater is treated on-site for metals precipitation and clarification prior to being discharged to the local POTW. All other wastes are shipped off-site for treatment, stabilization and landfill disposal.

### 1.2 Corporate Hazardous Waste Reduction Policy

It is the policy of USC to operate its facility both with the highest regard for the protection of human health and the environment, and in accordance with applicable federal, state and local environmental laws and regulations. Furthermore, it is USC's long term goal to: 1) Reduce the overall quantity of hazardous waste(s) generated; and/or 2) Recover, reuse or recycle any hazardous wastes generated when possible. To that end, USC has already initiated various waste reduction efforts over the past several years.

USC's management has authorized its General Manager to implement those waste reduction measures which have been deemed technically feasible and economically practical. This individual is also responsible for implementing both the hazardous waste reduction policy and the provisions of the Hazardous Waste Reduction Plan (HWRP).

USC's primary goal is to maintain its existing waste reduction efforts in a manner which maximizes efficiency and effectiveness. The use of "Porous Pots" in the plating baths has helped reduce waste Chromic Acid solution by removing impurities and extending the life of this process solution. USC will also continue to monitor industry research regarding more efficient methods of managing or recovering the alkaline stripping solution and minimizing the amount of wastewater from the electroplating process. To enhance these efforts, USC plans to provide employee training focusing on the implementation, benefits and applicability of waste reduction measures. Achieving this goal will reduce both disposal costs and the regulatory requirements for hazardous wastes generated throughout the facility.

### 2.0 HAZARDOUS WASTE GENERATION

### 2.1 General

During calendar year 2014, USC generated a total of 27.6 tons of RCRA hazardous wastes that were shipped off-site. These wastes included the following:

- 1) 12.6 tons of Chromium Contaminated Debris (D007, D008);
- 2) 6.3 tons of Waste Chromic Acid Solution (D002, D007);
- 2.2 tons of Alkaline Stripping Solution (D002, D007);
- 3.0 tons of Hazardous Waste Treatment Plant Filter Cake (F006);
- 5) 3.5 tons of Chromic Acid Tank Sludge (D002, D007)

In addition, a total of 375 tons of hazardous process wastewater were treated on-site before being discharged to the local POTW. There were no acute hazardous wastes generated by USC during 2014.

### 2.2 Hazardous Waste Streams

As indicated above, nearly all of the reportable hazardous wastes generated by USC result directly from the facility's cleaning and processing of metal parts. The primary cleaning operation involves submersing (stripping) the parts in an alkaline solution (Tetra Potassium Pyrophosphate - TKPP) and then rinsing the parts with fresh water. Over time, the alkaline solution may become spent and have to be disposed. This disposal process typically occurs about once every two years. The parts are then charged and placed in an electroplating bath containing Chromic acid. Wastes generated from this process may include waste Chromic acid solution and Chromic acid tank sludge that are removed from the electroplating bath tanks. The plated parts are then rinsed, and the rinse water is treated in the on-site wastewater treatment system via metal precipitation and clarification. The water treatment system includes a filter press which results in production of a filter cake waste. The final waste stream consists of debris produced during processing, including gloves, tape, floor sweepings and other ancillary materials.

Of the various hazardous wastes generated by USC during 2014, three of the six waste streams will be addressed in this HWRP update including Chrome contaminated debris, waste chromic acid solution and process wastewater. These wastes were all generated in amounts greater than five tons and together accounted for more than 90% of the total hazardous waste generated in 2014. The remaining hazardous wastes (alkaline stripping solution, chromic acid tank sludge and wastewater treatment plant filter cake) were generated at a rate below the five ton reporting threshold, and are not further addressed in this HWRP.

### 2.3 Production Rate Index

A Production Rate Index (PRI) has been developed for this facility to measure, and account for, changes in the annual amount of parts processed. These data will be used to facilitate the assessment of hazardous waste reduction efforts by allowing USC's management to distinguish inter-year quantity changes that resulted from waste reduction activity from those caused by economic and/or other factors. The PRI for Calendar Year 2014 was calculated based on past production information provided by USC personnel, as follows:

2014 Production = \$2,026,290 2013 Production = \$2,335,708

Production Rate Index = \$2,026,290 / \$2,335,708 = 0.87

### 2.4 Hazardous Waste Management Costs

To date, the costs of managing USC's hazardous wastes have resulted from the following activities (based on USC estimates):

Labor and Materials for Waste Management (Annual)

Labor (i.e., operators, technicians): \$45,567
Other/Miscellaneous Expenses: 2,885
Transportation & Disposal of Wastes (Annual): 19,059

Total \$ 67,511

### 3.0 HAZARDOUS WASTE STREAM REDUCTION MEASURES

### 3.1 General

As indicated in the previous sections, USC's hard chrome plating operations may result in the generation of several different types of hazardous waste. USC has already committed resources to determining and evaluating various measures for reducing the facility's overall hazardous waste generation rate and volume. The waste reduction measures which are currently utilized (and/or scheduled for implementation) at this facility include research regarding more efficient methods of managing or recovering the alkaline stripping solution, minimizing debris associated with the plating process, and minimizing the amount of wastewater from the electroplating process. Additionally, enhanced employee training will be pursued to improve waste management. These measures are discussed below.

### 3.2 Waste Reduction Measures

To minimize the quantity of hazardous wastes produced, USC has already implemented various production-related activities. These include limited use of Porous Pots in the Chromic acid baths to prolong process solution life and reduce tank sludges and continued use of the treatment system sludge dryer to reduce sludge weight. In addition, the implementation of new methods of masking parts to be plated has continually reduced the generation rate for this waste over time. USC is also committed to reviewing industry journals and trade publications for improved methods of using the alkaline cleaning solution. Reduced waste production may result from lengthening the useful life of the solution by filtration, by-product removal, etc., although no solution has been identified to date. The investigation into reducing the amount of wastewater produced from rinsing plated parts concluded with the selection of a lower flow rinsing nozzle, with the recirculation of rinse waters being allowed for some select operations.

Another waste reduction technique which is continually being used by USC is employee training. Currently, all personnel, regardless of their possible exposure to hazardous materials and/or hazardous wastes, receive OSHA Hazard Communications Standard training. RCRA Hazardous Waste training is also provided to a select group of employees that are involved with hazardous waste management or generation. These training programs are provided annually and cover a variety of topics including, but not limited to, compliance with applicable federal and state regulations; solid and hazardous waste identification definitions; sources of hazard information; the "cradle to grave" waste tracking system and employee responsibilities regarding waste identification and characterization. USC will continue to revise and expand these training programs to include additional information focusing on hazardous waste reduction. Among the new topics proposed are applicable waste reduction regulations, corporate waste reduction policy, benefits and incentives for hazardous waste reduction, and implementation of waste reduction techniques. Continued improvements in facility housekeeping, minor changes in operating practices and the installation/use of additional control equipment (e.g. splash guards on plating tanks) remain planned for 2015. These measures are designed to provide a cleaner, safer work environment at the USC facility and should ultimately lead to a reduction in the amount of chromium-contaminated debris and other wastes generated.

### 4.0 IMPACT OF WASTE REDUCTION IMPLEMENTATION

### 4.1 Schedule

The proposed schedule of implementation for the proposed waste reduction measures identified in Section 3.2 is summarized in Table 2.

### 4.2 Future Waste Transference Estimate

The implementation of the proposed waste reduction techniques identified in Section 3.2 will not result in the transference of waste to any other environmental media. The continued training program will provide employees with valuable information on the benefits of waste reduction and include basic techniques for reducing wastes at the USC facility. This program should help to promote the concept of waste reduction throughout the facility.

### 4.3 Economic Practicality

When adjusted for the production rate decrease between 2013 and 2014 (13 percent), the actual cost savings have increased due to increased labor costs and other miscellaneous expenses. In 2014, USC estimated the total cost of managing and disposing hazardous waste to be \$67,511. Future waste management costs will be estimated with more production and waste generation data. Implementation of USC's waste reduction measures will continue to be evaluated relative to hazardous waste generation volume, management cost, and production. Estimation of cost savings will be reported in future Hazardous Waste Reduction Plans.

### 4.4 Waste Reduction Assessments

The measurement of waste reduction effectiveness was completed for each reportable hazardous waste stream generated by USC during 2014. The waste reduction measurement was completed using a method developed and identified in USC's CY 1996 Hazardous Waste Reduction Plan, with the exception of the calculation of the Actual Hazardous Waste Reduction Rate presented below as Step 5. This calculation has been modified to reflect an example obtained from the NYSDEC during 2000.

### **Chrome Contaminated Debris**

Step 1 Percentage change (C) in the waste stream's generation volume from one year to the next (Note: A negative number represents a reduction in the generation volume):

### Comparing 2014 to 2013 (Prior Year)

C = (Waste current year [2014]) - (Waste prior year [2013]) x 100 (Waste prior year [2013])

C = 
$$\frac{(12.6 - 8.1)}{(8.1)}$$
 = 0.55 x 100

C = 55% Volume increase from 2013 (Prior Year) to 2014

### Comparing 2014 to 2003 (Base Year)

C = (Waste current year [2014]) - (Waste base year [2003]) x 100 (Waste base year [2003])

C = 
$$(12.6 - 3.47)$$
 = 2.63 x 100 (3.47)

C = 263% Volume increase from 2003 (Base Year) to 2014

Step 2 Production Rate Index (PRI) (Note: A number less than 1.0 will represent a reduction in the facility's production):

### Comparing 2014 to 2013 (Prior Year)

PRI = (Production current year [2014]) (Production prior year [2013])

PRI = 
$$(\$2,026,290)$$
  
(\\$2,335,708)

PRI = 0.87

### Comparing 2014 to 2003 (Base Year)

PRI = (Production current year [2014]) (Production base year [2003])

PRI = (\$2,026,290)(\$1,266,404)

PRI = 1.60

Step 3 Expected amount of hazardous waste generated (EHW) in 2014 relative to production in previous year (2012) and base year (2003):

### Comparing 2014 to 2013 (Previous Year)

EHW = 2014/2013 PRI x Hazardous waste generated during 2013:

EHW =  $0.87 \times 8.1 \text{ tons}$ 

EHW = 7.05 tons (expected in 2014)

### Comparing 2013 to 2003 (Base Year)

EHW = 2014/2003 PRI x hazardous waste generated during 2003:

EHW =  $1.60 \times 3.47 \text{ tons}$ 

EHW = 5.55 tons (expected in 2014)

Hazardous Waste Reduction (HWR) for CY 2013 represents the theoretical volume of increase or decrease of the current year's actual generated waste volume relative to the volume of hazardous waste "expected" to be generated when accounting for production differences between the previous/current year and base/current year [Note: A negative number indicates an increase in volume of hazardous waste generated (adjusted for production)]:

### Comparing 2014 to 2013 (Previous Year)

HWR = 2014/2013 EHW - Actual hazardous waste generated during 2014.

HWR = 7.05 tons - 12.6 tons

HWR = -5.55 tons adjusted hazardous waste increase from 2013 to 2014.

### Comparing 2014 to 2003 (Base Year)

HWR = 2014/2003 EHW - Actual hazardous waste generated during 2014.

HWR = 5.55 tons - 12.6 tons

HWR = -7.05 tons adjusted hazardous waste increase from 2003 to 2014.

Step 5 Estimate of the actual hazardous waste reduction rate (RR) achieved is a representation of the percentage difference between the Expected Hazardous Waste volume (relative to production) and the theoretical Hazardous Waste Reduction (or increase) volume [Notes: A negative number indicates an increase of hazardous waste generated for the current year, expressed as a percentage of the Expected Hazardous Waste (which is adjusted for production)]:

Using 2014/2013 (Previous Year) HWR & EHW

RR =  $\frac{2014/2013 \text{ HWR}}{2014/2013 \text{ EHW}} \times 100$ 

RR = -5.55 tons = 0.78 X 1007.05 tons

RR = 78% increase from 2013 to 2014

Using 2014/2003 (Base Year) HWR & EHW

 $RR = \frac{2014/2003 \text{ HWR}}{2014/2003 \text{ EHW}} \times 100$ 

RR = -7.05 tons = -1.27 X 1005.55 tons

RR = 127% increase from 2003 to 2014

### Waste Chromic Acid Solution

Step 1 Percentage change (C) in the waste stream's generation volume from one year to the next (Note: A negative number represents a reduction in the generation volume):

### Comparing 2014 to 2013

C = (Unit waste current year [2014]) - (Unit waste prior year [2013]) x 100 (Unit waste prior year [2013])

C = 
$$(6.3 - 6.9)$$
 = -0.09 x 100 (6.9)

C = 9% Volume decrease from 2013 to 2014

Comparing 2014 to 1996 (Base Year)

- C = (Waste current year [2014]) (Waste base year [1996]) x 100 (Waste base year [1996])
- C =  $(6.3 5.66) = 0.11 \times 100$ (5.66)
- C = 11% Volume increase from 1996 (Base Year) to 2014
- Step 2 Production Rate Index (PRI) (Note: A number less than 1.0 will represent a reduction in the facility's production):

Comparing 2014 to 2013 (Prior Year)

PRI = (Production current year [2014]) (Production prior year [2013])

PRI = (\$2,026,290)(\$2,335,708)

PRI = 0.87

Comparing 2014 to 2003 (Base Year)

PRI = (Production current year [2014]) (Production base year [2003])

PRI =  $\frac{(\$2,026,290)}{(\$1,266,404)}$ 

PRI = 1.60

Step 3 Expected amount of hazardous waste generated (EHW) in 2014 relative to production in previous year (2013) and base year (1996):

Comparing 2014 to 2013 (Previous Year)

EHW = 2014/2013 PRI x Hazardous waste generated during 2013:

EHW =  $0.87 \times 6.9 \text{ tons}$ 

EHW = 6.0 tons (expected in 2014)

Comparing 2014 to 1996 (Base Year)

EHW = 2014/1996 PRI x hazardous waste generated during 1996:

EHW =  $1.6 \times 5.66 \text{ tons}$ 

EHW = 9.06 tons (expected in 2014)

Step 4 Hazardous Waste Reduction (HWR) for CY 2014 represents the theoretical volume of increase or decrease of the current year's actual generated waste volume relative to the volume of hazardous waste "expected" to be generated when accounting for production differences between the previous/current year and base/current year [Note: A negative number indicates an increase in volume of hazardous waste generated (adjusted for production)]:

### Comparing 2014 to 2013 (Previous Year)

HWR = 2014/2013 EHW - Actual hazardous waste generated during 2014.

HWR = 6.0 tons - 6.3 tons

HWR = -0.3 tons adjusted hazardous waste increase from 2013 to 2014.

### Comparing 2014 to 1996 (Base Year)

HWR = 2014/1996 EHW - Actual hazardous waste generated during 2014.

HWR = 9.06 tons - 6.3 tons

HWR = 2.76 tons adjusted hazardous waste decrease from 1996 to 2014.

Step 5 Estimate of the actual hazardous waste reduction rate (RR) achieved is a representation of the percentage difference between the Expected Hazardous Waste volume (relative to production) and the theoretical Hazardous Waste Reduction (or increase) volume [Note: A negative number indicates an increase of hazardous waste generated for the current year, expressed as a percentage of the Expected Hazardous Waste (which is adjusted for production)]:

### Using 2014/2013 (Previous Year) HWR & EHW

RR =  $\frac{2014/2013 \text{ HWR}}{2014/2013 \text{ EHW}} \times 100$ 

RR = <u>-0.3 tons</u> = -0.05 X 100 6.0 tons

RR = 5% increase from 2013 to 2014

### Using 2014/1996 (Base Year) HWR & EHW

RR =  $\frac{2014/1996 \text{ HWR}}{2014/1996 \text{ EHW}} \times 100$ 

RR =  $\frac{2.76 \text{ tons}}{9.06 \text{ tons}} = 0.30 \text{ X } 100$ 

RR = 30% decrease from 1996 to 2014

### Process Wastewater

Step 1 Percentage change (C) in the waste stream's generation volume from one year to the next (Note: A negative number represents a reduction in the generation volume):

### Comparing 2014 to 2013

C = (Unit waste current year [2014]) - (Unit waste prior year [2013]) x 100 (Unit waste prior year [2013])

C = 
$$\frac{(375 - 432)}{(432)}$$
 = -0.13 x 100

C = 13.0% Volume decrease from 2013 to 2014

### Comparing 2014 to 1995 (Base Year)

C = (Waste current year [2014]) - (Waste base year [1995]) x 100 (Waste base year [1995])

$$C = (375 - 228) = 0.65 \times 100$$
(228)

C = 65% Volume increase from 1995 (Base Year) to 2014

Step 2 Production Rate Index (PRI) (Note: A number less than 1.0 will represent a reduction in the facility's production):

Comparing 2014 to 2013 (Prior Year)

PRI = (Production current year [2014]) (Production prior year [2013])

PRI = 
$$($2,026,290)$$
  
(\$2,335,708)

PRI = 0.87

### Comparing 2014 to 2003 (Base Year)

PRI = (Production current year [2014]) (Production base year [2003])

PRI = (\$2,026,290)(\$1,266,404)

PRI = 1.60

Step 3 Expected amount of hazardous waste generated (EHW) in 2013 relative to production in previous year (2012) and base year (1995):

### Comparing 2014 to 2013 (Previous Year)

EHW = 2014/2013 PRI x Hazardous waste generated during 2013:

EHW =  $0.87 \times 432 \text{ tons}$ 

EHW = **376.0** tons (expected in 2013)

### Comparing 2013 to 1995 (Base Year)

EHW = 2014/1995 PRI x hazardous waste generated during 1995:

EHW =  $1.60 \times 228 \text{ tons}$ 

EHW = **364.8 tons** (expected in 2014)

Hazardous Waste Reduction (HWR) for CY 2013 represents the theoretical volume of increase or decrease of the current year's actual generated waste volume relative to the volume of hazardous waste "expected" to be generated when accounting for production differences between the previous/current year and base/current year [Note: A negative number indicates an increase in volume of hazardous waste generated (adjusted for production)]:

### Comparing 2014 to 2013 (Previous Year)

HWR = 2014/2013 EHW - Actual hazardous waste generated during 2014.

HWR = 376 tons - 375 tons

HWR = 1 ton adjusted hazardous waste decrease from 2013 to 2014.

### Comparing 2014 to 1995 (Base Year)

HWR = 2014/1995 EHW - Actual hazardous waste generated during 2014.

HWR = 365 tons - 375 tons

HWR = 10 tons adjusted hazardous waste increase from 1995 to 2014.

Step 5 Estimate of the actual hazardous waste reduction rate (RR) achieved is a representation of the percentage difference between the Expected Hazardous Waste volume (relative to production) and the theoretical Hazardous Waste Reduction (or increase) volume [Note: A negative number indicates an increase of hazardous waste generated for the current year, expressed as a percentage of the Expected Hazardous Waste (which is adjusted for production)]:

### Using 2014/2013 (Previous Year) HWR & EHW

RR = 2014/2013 HWR x 100 2014/2013 EHW

RR =  $\frac{1 \text{ ton}}{376 \text{ tons}}$  = 0.003 X 100

RR = 0.3% decrease from 2013 to 2014

### Using 2014/1995 (Base Year) HWR & EHW

RR =  $\frac{2014/1995 \text{ HWR}}{2014/1995 \text{ EHW}} \times 100$ 

RR =  $\frac{-10 \text{ tons}}{365 \text{ tons}}$  = 0.03 X 100

RR = 3% increase from 1995 to 2014

COMPANYNAME US Chrome Corporation of New York	A LD. NUMBER NYD990774200

### TABLE 1

PRODUCTIVITY INDEX BASE INDEX = 1 (YEAR HWRP FIRST SUBMITTED) 1995 1996 1997 1998	0.33 3.0 0.2		0.30 0.94 0.33		1.28 0.664 0.652		1.28 0.664 0.652	0.09 1.496 0.4			
BASE INDEX =					0.55		0.62				
1998	9.87		6.60		3.34		260.54	8.73			
QUANTITY OF WASTE GENERATED 1996 1997	1.19		2.33		2.37		263.8	3.65			
ANTITY OF WASTE (TONS) 1996 1	6.44		2.63		2.1		266.5	5.66			
QU,					8.1		228				
DISPOSAL METHOD	Treat/Recycle		Stabilization	& Secure Landfill	Stabilization	& Secure Landfill	On-Site Treatment	Treatment &	Secure Landfill		
SOURCE OF GENERATION	Plating solution	with impurities	Sediment on	bottom of tank	WW Metals removal		Plating & Rinsing	Spent Alkaline	Strip Solution		
NAME OF WASTE	Chromic Acid	Solution (D)	Chromic Acid	Tank Sludge (E)	Waste Treatment	Filter Cake (A)	waste Water (B)	Stripping Solution			
WASTE STREAM ID NUMBER	001		002		003		004	900			

THIS FORM DEVELOPED BY; THE NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION DIVISION OF SOLID & HAZARDOUS MATERIALS, BUREAU OF WASTE REDUCTION & RECYCLING

Chrome Corpora
----------------

TABLE 1 (continuation #1)

WASTE STREAM ID	NAME OF WASTE	SOURCE OF GENERATION	DISPOSAL METHOD	nò	QUANTITY OF WASTE GENERATED (TONS)	STE GENERATE NS)	a	BASE INDE	PRODUCTIN X = 1 (YEAR I	PRODUCTIVITY INDEX BASE INDEX = 1 (YEAR HWRP FIRST SUBMITTED)	UBMITTED)
NUMBER				1999	2000	2001	2002	1999	2000	2001	2002
001	Chromic Acid	Plating Solution	treat/Recycle	3.80	6.25	00.00	00.0	1.5	1.2	1.3	76-0
	Solution (D)	with impurities									
002	Chromic Acid	Sediment on	Stabilization	0.44	3.90	0.30	1.6	0.11	6.0	08.0	76.0
	Tank Sludge (E)	Bottom of Tank	& Secure Landfill								
003	Waste Treatment	WW Metals removal	Stabilizaion	4.02	3.21	3.13	1.51	0.640	0.631	0.623	76.0
	Filter Cake (A)		& Secure Landfill								
		1									
004	Waste Water (B)	Plating & Rinsing	On site Treatment	264.68	258.21	253,98	1017.0	0.642	0.631	0.623	76.0
900	Stripping Solution	Spent Alkaline	Treatment &	8.15	3.48	5.44	6.05	0.45	0.40	0.42	76.0
		Strip Solution	Secure Landfill								
	13.	THE COPY DEVELORED BY THE	THE NEW YORK STATE BEDIEFING TO THE STATE OF				10.00				1

THIS FORM DEVELOPED BY: THE NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION DIVISION OF SOLID & HAZARDOUS MATERIALS, BUREAU OF WASTE REDUCTION & RECYCLING

EPALD NUMBER NYD990774200
---------------------------

### TABLE 1

WASTE STREAM ID NUMBER	NAME OF WASTE	SOURCE OF GENERATION	DISPOSAL METHOD	QU 2003	QUANTITY OF WASTE GENERATED  (TONS) 2005	STE GENERATE NS) 2005	2006	BASE INDEX = 2003	PRODUCTIVITY INDEX BASE INDEX = 1 (VEAR HWRP FIRST SUBMITTED) 2003 2004 2005 2006	IV INDEX RP FIRST SUI	BMITTED)
100	Chromic Acid	Plating solution	Treat/Recycle	8.89	3.79	2.24	3.05	0.99	1.47	96.0	1.13
	Solution (D)	with impurities									
002	Chromic Acid	Sediment on	Stabilization	1.66	2.15	2.80	1.40	66.0	1.47	96.0	1.13
	Tank Sludge (E)	bottom of tank	& Secure Landfill								
003	Waste Treatment	WW Metals removal	Stabilization	5.94	9.55	9.33	3.75	0.99	1.47	96.0	1.13
	Filter Cake (A)		& Secure Landfill								
004	waste Water (B)	Plating & Rinsing	On-Site Treatment	722.0	0.086	571.0	421.17	66.0	1.47	96.0	1.13
900	Stripping Solution	Spent Alkaline	ent &	2.13	2.84	6.40	6.88	66.0	1.47	96.0	1.13
		Strip Solution	Secure Landfill								
900	Chrome Debris	Tape,gloves, etc.	Stabilizartion	3.47	5.80	15.0	11.4	66.0	1.47	96.0	1.13
			& Secure Landfill								

THIS FORM DEVELOPED BY: THE NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION DIVISION OF SOLID & HAZARDOUS MATERIALS, BUREAU OF WASTE REDUCTION & RECYCLING

COMPANY NAME U.S. Chrome Corporation of New York	PA.LD. NUMBER NYD990774200

TABLE 1 (continuation #1)

WASTE	NAME OF WASTE	SOURCE OF GENERATION	DISPOSAL METHOD	19	JANTITY OF WA	QUANTITY OF WASTE GENERATED (TONS)	93	BASE INDE	PRODUCTI X = 1 (YEAR)	PRODUCTIVITY INDEX BASE INDEX = 1 (YEAR HWRP FIRST SUBMITTED)	UBMITTED)
NUMBER				2007	2008	2009	2010	2007	2008	2009	2010
001	Chromic Acid	Plating Solution	Treat/Recycle	5.95	8.75	10.85	3.0	1.0	1.32	77.0	0.94
	Solution (D)	with impurities									
					3100	77 = 27 = 3					
002	Chromic Acid	Sediment on	Stabilization	3.85	7.0	7.0	0.35	1.0	1.32	77.0	0.94
	Tank Sludge (E)	Bottom of Tank	& Secure Landfill								
003	Waste Treatment	WW Metals removal	Stabilizaion	2.25	3.75	0.75	0.75	1.0	1.32	77.0	0.94
10 mm and 10 mm	Filter Cake (A)		& Secure Landfill								
004	Waste Water (B)	Plating & Rinsing	On site Treatment	417	462.3	500.4	362.8	1.0	1.32	0.77	0.94
900	Stripping Solution	Spent Alkaline	Treatment &	2.75	8.25	0	9.05	1.0	1.32	0.77	0.94
		Strip Solution	Secure Landfill								
900	Chrome Debris	Tape,gloves,etc.	Stabilization	4.8	7.2	8.5	4.5	1.0	1.32	77.0	0.94
			& Secure Landfill								
	T	THIS FORM DEVEL OBER BY TH	THE NEW YORK STATE REBARDINGS TO ENIVIRONIA FAITAL CONSERVATION	TATE OF	PARTITIONAL	TATALA	OID LIVE DIS				

THIS FORM DEVELOPED BY THE NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION DIVISION OF SOLID & HAZARDOUS MATERIALS, BUREAU OF WASTE REDUCTION & RECYCLING

COMPANYNAME US Chrome Corporation of New York	EPALD. NUMBER NYD990774200

### TABLE 1

Chromic Acid   Plating solution   Treat/Recycle   9.4   3.6   6.9   6.3	WASTE STREAM ID NIMBED	NAME OF WASTE	SOURCE OF GENERATION	DISPOSAL METHOD	00V	QUANTITY OF WASTE GENERATED	TE GENERATE S)	D 2014	BASE INDEX = 1 (YEAR HWRP FIRST SUBMITTED)	PRODUCTIVII	TY INDEX	SMITTED)
Solution (D)   With impurities	001	Chromic Acid	plating solution	Treat/Recycle	9.4	3.6	6.9	6.3	1.46	1.05	0.78	0.87
Chromic Acid Sediment on Stabilization 1.5 0 4.2 3.5 1.46 1.05  Tank Sludge (E)			with impurities									
Tank Sludge (E)												
Tank Sludge (E)         Dottom of tank         & Secure Landfill         1.5         2.1         3.6         3.0         1.46         1.05           3         Waste Treatment         WM Metals removal         \$tabilization         1.5         2.1         3.6         3.0         1.46         1.05           4         Waste Mater (A)         Plating & Rinsing         On-Site Treatment & 417         450         432         375         1.46         1.05           \$tripping Solution         Spent Alkaline         Treatment & 4.4         6.1         0.8         2.2         1.46         1.05           \$tripping Solution         Strip Solution         Secure Landfill         8.6         10.8         8.1         12.6         1.46         1.05           Chrome Debris         Tape, gloves, etc.         Stabilization         8.6         10.8         8.1         12.6         1.46         1.05	002			Stabilization		0	4.2	3.5	1.46	1.05	0.78	0.87
Waste Treatment   WW Metals removal   Stabilization   1.5   2.1   3.6   3.0   1.46   1.05		Sludge	of	Secure								
Maste Treatment   WW Metals removal   Stabilization   1.5   2.1   3.6   3.0   1.46   1.05												
# Waste Water (B) Plating & Rinsing On-Site Treatment 417 450 432 375 1.46 1.05    Stripping Solution   Spent Alkaline   Treatment & 4.4 6.1 0.8 2.2 1.46 1.05     Stripping Solution   Secure Landfill   Secure L	003			Stabilization	(8.1	2.1			1.46	1.05	0.78	0.87
4 Waste Water (B) Plating & Rinsing On-Site Treatment 417 450 432 375 1.46 1.05 stripping Solution Spent Alkaline Treatment & 4.4 6.1 0.8 2.2 1.46 1.05 strip Solution Secure Landfill 8.6 10.8 8.1 12.6 1.46 1.05		Cake		Secure								
# Waste Water (B) Plating & Rinsing On-Site Treatment 417 450 432 375 1.46 1.05  Stripping Solution Spent Alkaline Treatment & 4.4 6.1 0.8 2.2 1.46 1.05  Strip Solution Secure Landfill B.6 10.8 8.1 12.6 1.46 1.05  Chrome Debris Tape, gloves, etc. Stabilization & Secure Landfill B.6 10.8 8.1 12.6 1.46 1.05												
Stripping Solution         Spent Alkaline         Treatment & 4.4 6.1 0.8 2.2 1.46 1.05           Strip Solution         Secure Landfill         1.05           Chrome Debris         Tape, gloves, etc.         Stabilization & Secure Landfill         8.6 10.8 8.1 12.6 1.46 1.05	004	Water	ধ		417	450	432	375	1.46	1.05	0.78	0.87
Stripping Solution         Spent Alkaline         Treatment & 4.4         6.1         0.8         2.2         1.46         1.05           Strip Solution         Secure Landfill         8.6         10.8         8.1         12.6         1.46         1.05           Chrome Debris         Tape, gloves, etc.         Stabilization         8.6         10.8         8.1         12.6         1.46         1.05												
Chrome Debris Tape, gloves, etc. Stabilization & Secure Landfill 8.6 10.8 8.1 12.6 1.46 1.05	900	3500	Spent	Treatment &	4.4	6.1	8.0	2.2	4.	1.05	0.78	0.87
Chrome Debris Tape, gloves, etc. Stabilization 8.6 10.8 8.1 12.6 1.46 1.05				Secure Landfill								
Chrome Debris Tape,gloves, etc. Stabilization 8.6 10.8 8.1 12.6 1.46 1.05												
& Secure Landfill	900	Chrome Debris		Stabilization	9.8	0	8.1	12.6	1.46	1.05	0.78	0.87
				Secure								

THIS FORM DEVELOPED BY: THE NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION DIVISION OF SOLID & HAZARDOUS MATERIALS, BUREAU OF WASTE REDUCTION & RECYCLING

EPALD.NUMBER NYD990774200	The second secon
COMPANY NAME U.S. Chrome Corporation of New York	

TABLE 1 (continuation #1)

WASTE	NAME OF WASTE	SOURCE OF GENERATION	DISPOSAL METHOD	ð	UANTITY OF W.	QUANTITY OF WASTE GENERATED	Q3	BASE IND	PRODUCTIVITY INDEX BASE INDEX = 1 (VEAR HWRP FIRST SIRMITTED)	ITY INDEX	BMITTED
ID NUMBER				2011	2012	2013	2014	2011	2012	2013	2014
007	Waste De-burring	Finishing	Treatment & Secure Landfill	5.4	0	0	0	1.46	1.05	0.78	0.87
	Solution										
800	Waste Lacquer/	Unused/Expired	Stabilization & Secure Landfill	3.0	0	0	0	1.46	1.05	0.78	0.87
	Thinner	Materials									
		THIS EODM NEVEL OPEN BY THE NEW VORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION	F NFW VORK STATE DEPAI	RTMFNTOF	FNVIRON	MENTAL CO	NGFRVATIC	Z			

THIS FORM DEVELOPED BY THE NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION DIVISION OF SOLID & HAZARDOUS MATERIALS, BUREAU OF WASTE REDUCTION & RECYCLING

## HAZARDOUS WASTE REDUCTION PROGRAM

EPALD.NUMBER NYD990774200	
n of New York	
Chrome Corporation	
COMPANY NAME U.S.	

### TABLE 2

NAME OF WASTE	WASTE STREAM AFFECTED	REDUCTION PLANS/PROJECTS	ESTIMATED WASTE REDUCTION (TONS)	METHOD USED TO CALCULATE *ROI	*ROI (EST)	GOAL DATE	REMARKS	
Chromic Acid Solution (D002, D007)		a) Improved Efficiency		N/A	N/A			
		b) Employee Training	EŽ)					
Process Wastewater & Filter Cake		a) Improved Efficiency		N/A	N/A			
		b) Employee Training		N/A	N/A			
Stripping Solution		Quality Control		N/A	N/A			
Chrome Debris	Tape, Gloves, Etc.	a) Employee Training		N/A	N/A			
		b) Improved Housekeeping &						
Chromic Acid Tank Sludge		a) Improved Efficiency		N/A	N/A			
		b) Employee Training		N/A	N/A			

THIS FORM DEVELOPED BY THE NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION DIVISION OF SOLID & HAZARDOUS MATERIALS, BUREAU OF WASTE REDUCTION & RECYCLING

IRR = INCREASED RATE OF RETURN

AC = ANNUALIZED COST

\*ROI = RATE OF INVESTMENT

PI = PROFITABILITY INDEX

PP = PAYBACK PERIOD

NPV = NET PRESENT VALUE

U.S. POSTAGE PAID BATAVIA.NY 14020 FEB 29, 16 AMOUNT 00146579-04

United States Environmental protection agency Office of Federal activities

Route

International compliance Assurance Division Ariel Rius Building (2354 A)

1200 pennsylvania Avenue, NW

Washington, Dc. 20460

AHN: SCOTT NELSON

U S CHROME CORP OF NEW YORK 31 SWAN ST BATAVIA NY 14020

Certified

EPA Mail

NELSON,SCOTT

Mailstop: ARIEL RIOS NORTH

Department: 2254A